

 **MEYRA®**



inspire joy of life

1.610
iCHAIR MC1 LIGHT




TRIED AND TESTED ENTRY-LEVEL MODEL

iCHAIR MC1 LIGHT- THE INTELLIGENT ENTRY-LEVEL MODEL

- Electrical back angle adjustment from -10° to 50°
- Electrical tilt from -4° to 24°
- For relaxed positioning and effective pressure relief
- Use of VR2 electronics
- Available in three different seat widths
- Pull-out battery case enables simple and effective maintenance
- Split aluminium rims for quick and easy service
- High-grade impact-protected and powerful LED lighting for enhanced safety

iCHAIR
MC1 LIGHT
1.610





PRODUCT COMPARISON



iCHAIR MC BASIC

iCHAIR MC1

iCHAIR MC1 LIGHT

Speed in km/h	6	6	6 / 10
Seat widths in mm	430	430, 480	380, 430, 480
Electrical adjustment	-	Back / Tilt	Back / Tilt

Compare the advantages of the new iCHAIR MC1 LIGHT with its predecessors.
The iCHAIR MC BASIC and the iCHAIR MC1 will in future be replaced by the iCHAIR MC1 LIGHT.

SPECIFICATIONS



iCHAIR MC1 LIGHT

Seat width in mm	380 – 600
Width in mm	630 – 750 ¹⁾
Seat depth in mm	400 – 530
Lower leg length in mm	280 – 430
Seat height front (without seat cushion) in mm	440 / 480 / 510
Total height in mm	930 – 1,130 ²⁾
Back height in mm	480
Armrest height in mm	240 – 350
Length with / without footrest in mm	1,080 / 840
Transport length in mm	840
Transport width min. in mm	630
Transport height min. in mm	560 – 660
Wheel size, front, in mm	230 x 70 (9")
Wheel size, rear, in mm	356 x 75 (14")
Max. obstacle height in mm	60
Turning radius in mm	840
Ground clearance (battery tray) in mm	80
User weight in kg	130
Empty weight in kg	94 ³⁾
Permissible total weight in kg	224
Max. additional load in kg	10
Speed in km/h	6 / 10
Motor power in W	2 x 180 / 2 x 300
Range max. in km	30 ⁴⁾
Permitted uphill / downhill gradient	8,5° / 15%
Seat tilt, electrical, in degrees	-4° to 24° ⁵⁾
Back angle, electrical, in degrees	-10° to 50°
Seat tilt, mechanical, in degrees	0° / 4° / 10°
Back angle, mechanical, in degrees	-10° to 30°
Steering type	Indirect

Dimensional tolerances ± 10 mm, ± 2°, data subject to design changes

¹⁾ ready to move

²⁾ seating systems belt / ErgoSeat

³⁾ without armrests and legrests

⁴⁾ with 43 Ah (5h), 50 Ah (20h) battery

⁵⁾ adjustment range dep. on SH and castor wheel size max. +/- 3° deviation



Feel free to contact us:

MEYRA GmbH

Meyra-Ring 2
D-32689 Kalletal-Kalldorf

✉ info@meyra.de

Tel.: +49 5733 922 - 0
Fax: +49 5733 922 - 9311

www.meyra.de